

OPEX®

# OMATION® Low-Volume Mail Opener



## Why Series 210 Envelopener®?

The OMATIION® Series 210 Envelopener® offers mailroom automation for even the smallest quantities.

The Series 210™ Envelopener® is a compact tabletop unit ideal for operations opening between 200 and 2000 pieces per day. Utilizing state-of-the-art milling cutting technology, the Series 210 automatic envelope opener has the ability to open a wide range of envelopes, quickly and efficiently at rates up to 400 envelopes per minute.

## Features

---

### Specialized Cutting Technology

The milling cutter opens the envelope from edge-to-edge while minimizing cut contents and provides a soft, feathered edge which greatly reduces the risk of painful paper cuts.

### Digital Envelope Counter

The OMATIION® Series 210™ envelope opener has an easy to view counter display. The large capacity chip tray permits 3,500 envelopes to be opened before needing to be emptied.

### Self-Adjusting Feeder

The advanced self-adjusting feeder provides greater efficiency for mixed-mail opening. Additionally, the adjustable output tray easily accommodates flats and longer envelopes.

### Cut Depth Adjustment Knob

The cut depth adjustment knob has three optimal cut-depth settings to accommodate various mail types including, thin airmail envelopes, thick envelopes, and overnight envelopes. The no-cut setting is a fast and accurate way to count envelopes, including ballots.

## Advantages

---

### Eliminate waste

The milling cutter “chips” away the edge of the envelope and waste is channeled into a large capacity chip bin that can be easily emptied.

### Fast Mail Processing

This compact mailroom automation product seamlessly opens inbound mail at rates of up to 400 envelopes per minute.

### Operator Safety

A soft feathered edge minimizes painful papercuts and provides edge-to-edge opening for ease of content extraction.

### Small Footprint

The OMATIION® Series 210™ envelope opener is compact and requires minimal desktop space.

## Specifications

---

<b>Length</b>	40.3" (1023.6 mm)
<b>Depth</b>	16.5" (419.1 mm) or 18" (457.2 mm) with power cord
<b>Height</b>	14.3" (363.2 mm)
<b>Weight</b>	52 lbs (23.6 kg)
<b>Speed</b>	Up to 400 envelopes per minute (6" envelope)
<b>Envelope Sizes &amp; Types</b>	All sizes and types (including overnight envelopes)
<b>Thickness</b>	Up to .188" (4.8 mm)
<b>Depth of Cut</b>	From .01"-.07" (.25 mm - 1.79 mm)
<b>Electrical Requirements</b>	1964 BTU/h (max @ 115v/5A) 110-120 VAC, 60HZ, 5A
<b>Decibel Rating</b>	Does not exceed safety standard of 80 dB.

### Have questions?

Contact us.

 [digitizeyourdocuments.com](https://digitizeyourdocuments.com)

 [info@opex.com](mailto:info@opex.com)

**OPEX®**